


CONTROLLER QUOTATION ENQUIRY FROM





Customer-Branch Contact Name Project Reference
Contact No./email Required Date
Qube Traclite Hylite DD-MM-YY
No of Floors Contact Speed M/s Travel in Meters Simplex Duplex Wall Mounted Full Collective Full Collective Simple Collective
Motor Details Geared Gearless VF Hydraulic Standard Hydraulic Neutral Available Motor or Valve Manufacturer Motor FLC Starting Current Motor Volts Motor KW Motor HP Brake or Valve Voltage V AC/DC Watts VF Open Loop VF Closed Loop Star-Delta DOL Soft Start
Door Operator Model Additional Door Information
Advance Door Open Zone Locking Nudging Automatic Front Only Manual Non Selective Shortest Floor Height in Metres Swing Selective Include in Position Indicators table below* (Important Information)
Lift Positioning Method Note : Position Encoder for speeds above 1M/s Shaft Equipment
Magnet Switch Other Limit Switches Tapehead Halfway Terminal box 100Way Position Encoder Pulley Mounted On Lift Car Position Encoder OSG Mouted (Bode/PFB Governors) Limit Switches Halfway Terminal box 100Way Cartop Control
Landing Push Interface Note: Default Push Acceptance Supply 24vDC if different please give details below No. of Push Risers V AC/DC Watts
Stainless Steel Surface Mount Networked LOP Stainless Steel Surface Mount Extended 600mm Networked LOI
Position Indicators Lifteknic Indicator with Lens and Gong speaker kit LED LCD LED LCD LED LCD
Supplied by Others - Details req'd All Lifteknic Networked Devices are EN81-70 Compliant. Indicators Include Arrival Gong and Hall Lantern Feature. Push Nodes include EN81 Call-Acceptance Buzzer.
All devices are compatible with the controller internal 24VDC power supply & Include Plug-In Shaft Wiring for Fast Installation. Front*
Rear*
Standard Features Fire Control/Alarm Single VF Doors Speech Card
Idented Cable
Additional Information Note: Please provide as much information as possible to recieve an accurate quotation